


PTFE insulated heating cable

Isopad IS-KTeS is a preterminated PTFE insulated heating cable suitable for use where no excessive mechanical loads are expected and moisture may be present.

This flexible and easily installed cable provides inexpensive and versatile heating. Applications include heat tracing of pipes, small containers, tools, machines,

extremely thin and short pipes, and machine parts with limited mounting space.



Area Specifications

Area classification	Nonhazardous, ordinary area
Ingress protection	IP65
Electrical protection class	Class I
Maximum withstand temperature (power off)	260°C
Maximum withstand temperature (power on)	Depends upon power

Standard Manufacturing Sizes

Outer diameter (OD)	2.5 to 3.5 mm
---------------------	---------------

Heater Construction

Type	Resistance heating cable
Material	Various alloys
Material of insulation	PTFE
Material of outer sheath	Copper-nickel braid

Lead Connection

Connection length	Terminated at each end with a 1.5 m cold lead
Cross section	1.0 mm ²
Maximum operating temperature	260°C
Insulation material	PTFE

Technical Data

Frequency	50-60 Hz
Nominal operating voltage	230 Vac
Power per meter	20 W/m
Maximum operating temperature	260°C
Minimum bend radius	10 mm
Minimum spacing	5 mm

Ordering Information

	Part number	Length⁽¹⁾ (m)	Nominal Power⁽²⁾ (W)	Nominal Voltage (Vac)
	680108-000	2.20	50	230
	970664-000	4.40	100	230
	414978-000	7.00	140	230
	869130-000	11.00	250	230
	037962-000	16.00	330	230
Other lengths and power specifications, etc., available upon request	927424-000	22.00	500	230
	073216-000	28.00	630	230
	206840-000	40.00	920	230
	736072-000	58.00	1300	230
	380470-000	80.00	1740	230
	480964-000	112.00	2360	230
	335974-000	156.00	3120	230

⁽¹⁾ Tolerances \pm (2% + 100 mm)

⁽²⁾ Tolerances \pm 10%

Worldwide Headquarters**Tyco Thermal Controls**

7433 Harwin Drive
Houston, TX 77036

USA

Tel: 800-545-6258

Tel: 650-216-1526

Fax: 800-527-5703

Fax: 650-474-7711

info@tycothermal.com

www.tycothermal.com

Canada**Tyco Thermal Controls**

250 West St.

Trenton, Ontario

Canada K8V 5S2

Tel: 800-545-6258

Fax: 800-527-5703

Latin America**Tyco Thermal Controls**

7433 Harwin Drive

Houston, TX 77036

United States

Tel: 713-868-4800

Tel: 713-735-8645

Fax: 713-868-2333

Europe, Middle East, Africa (EMEA)**Tyco Thermal Controls**

Romeinse Straat 14

3001 Leuven

België / Belgique

Tel: +32 16 213 511

Fax: +32 16 213 603

Asia Pacific**Tyco Thermal Controls**

20F, Innovation Building

1009 Yi Shan Rd

Shanghai 200233

P.R.China

Tel: +86 21 2412 1688

Fax: +86 21 5426 2937 / 5426 3167

Tyco, Alliance Integrated Systems, AMC, AutoMatrix, AutoSol, BTV, CapaciSense, Chemelex, DHSX, DigiTrace, DigiTrace logo, DigiTrace Supervisor, Duoterm, ElectroMelt, EM2XR, FHSM, FHSC, FlexFit, FlexiClic, Flowguard, FreezeTrace, FreezGard, Frostex, Flostex Plus, Frostguard, FroStop, FSE, Gardian, HAK, Handvise, HBTV, HCCL, HotCap, HQT, HTPG, HTP, HWAT, HXTV, IceStop, Interlock, Isocable, Isodrum, Isoheat, Isomantle, Isopad, Isopad Frostguard, Isopad logo, Isopanel, Isotape, Isotherm, JBM, JBS, K-Flex, K-Flex logo, KHE, KHH, KHL, KHP, KTV, Labsafe, LBTV, LHC, LHFV, LHRV, Metabond, Mini WinterGard, Miser WinterGard, MoniTrace, Multi-plus, NGC, PetroTrace, PLI, PolyMatrix, Pyro CiC, PyroFLX, Pyromaster, Pyropak, Pyrosil, PyroSizer, Pyrotenax, Pyrotenax Designer, Pyrotenax logo, QTVR, QuickNet, QuickNet logo, QuickStat, QuickTerm, RayClic, RaySol, RayStat, Retro WinterGard, RHS, RHSC, RHSM, RMM2, SBF, SBV, SC, SHC, Sheathmaster, ShowerGuard, SLBTV, Smart heat for Comfort and Safety, SnoCalc, SnoCalc logo, STS, System 500, System 1850, System 1850-SE, System 2000, System 2200, T2, T2 logo, T2Blue, T2QuickNet, T2Red, T2Reflecta, TankCalc Plus, TempBus, Thermoheat, ThermoLimit, Thermo-Line, Total Care in Heat-tracing, Touch, Trac-Loc, Trac Calc, TraceCalc Net, TraceCalc Net logo, TraceCalc Pro logo, TraceGuard 277, TraceMaster, Tracer, Tracer logo, TRACERLYNX, TRACERLYNX logo, TraceStat, TraceTek, TraceTek logo, TruckPak, VLBT, VLKTV, VPL, We manage the heat you need, WinterGard, WinterGard logo, WinterGard Plus, WinterGard Wet, XL-ERATE, XL-ERATE logo, XL-Trace, XTV and Zero EMI are registered and/or unregistered trademarks of Tyco Thermal Controls LLC or its affiliates.

All other trademarks are the property of their respective owners.

tyco

Thermal Controls

Important: All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their particular application. Tyco Thermal Controls makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. Tyco Thermal Controls' only obligations are those in the Tyco Thermal Controls Standard Terms and Conditions of Sale for this product, and in no case will Tyco Thermal Controls or its distributors be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of the product. Specifications are subject to change without notice. In addition, Tyco Thermal Controls reserves the right to make changes—without notification to Buyer—to processing or materials that do not affect compliance with any applicable specification.