

# » TWISTLOC

## Quick-change nozzle system




### Lechler TWISTLOC, nozzle changing in less than no time.

Save time and money with the quick-change nozzle system.

- **Quick:**  
It takes just one twist to install or remove the nozzle.
- **Easy:**  
Can be installed without tools – even in difficult-to-access locations and in bad lighting conditions.
- **Safe:**  
Installation errors are avoided, as the nozzles are always set to the correct direction.
- **Max. pressure:**  
15 bar.



System components		Ordering no.							Inner Ø D [mm]	Weight [g]	
		Type	Mat. no.				Code				
			1C	16	5E	7A	1/4 BSPT	3/8 BSPT			Welded connec- tion
Threaded nipple		092.102	●				CC		8.0	25.0	
		092.102	●					CE		11.6	25.0
		092.102			●				CE		8.0
Welded nipple		092.104	●					00	11.6	45.0	
Gasket for material 304 SS and 303 SS		092.113							-	1.0	
Gasket for material PVDF		092.115							-	1.0	
Gasket, incl. rubber gasket ring for use with non-return valves or strainers		092.116							-	2.0	
Gasket, incl. rubber gasket ring for use with non- return valves or strainers, for PVDF material		092.114							-	2.0	
Quick-release system For nozzle series 652/679		092.106	●	●					-	20.0 (stainless steel)	
Quick-release system For nozzle series 226/468/684		092.108	●	●					-	20.0 (stainless steel)	



Ordering Type + Material no. + Code = Ordering no.  
example: 092.102 + 16 + CC = 092.102.16.CC